









# TRETRICE PLUMBING PRODUCTS

## 800B UTILITY GAUGE



The Trerice 800B Utility Gauge is designed for general pressure indication requirements. This gauge provides excellent accuracy (1.6% full scale) and reliability at an economical cost. The case is drawn steel and wetted parts are brass.

SPECIFICATIONS	800B UTILITY GAUGE
Model	800B
Dial Sizes	1 1/2" (40mm), 2" (50mm), 2 1/2" (63mm), 4" (100mm)
Wetted Parts	Bronze tube, brass socket
Movement	Brass
Connection	1/8 NPT (not available with 4" dial size) 1/4 NPT (not available with 1 1/2" dial size)
Case	Drawn steel, black finished, stem-mounted flangeless
Window	Acrylic
Pointer	Steel, black painted
Dial Face	Aluminum, white background with black graduations and markings
Accuracy	1.6% Full Scale
Maximum Temperature	180° F (82° C)
Approximate Shipping Weight	1 1/2": 0.2 lbs. (0.09 kg)      2": 0.3 lbs. (0.14 kg) 2 1/2": 0.3 lbs. (0.14 kg)      4": 0.6 lbs. (0.27 kg)

### How To Order (Example 800B 2502 L A 110)

Model	Dial Size	Connection Size	Connection Location	Units of Measure	Range Code
800B	15    1 1/2"	01    1/8 NPT	L    Lower	A    psi	See Range Table
	20    2"	02    1/4 NPT	B    Back	D    psi/kPa	
	25    2 1/2"				
	40    4"				

Range Codes	Specific Ranges
010	30" Hg to 0
020	30" Hg to 15 psi
030	30" Hg to 30 psi
040	30" Hg to 60 psi
050	30" Hg to 100 psi
060	30" Hg to 150 psi
070	30" Hg to 300 psi

Range Codes	Specific Ranges
080	0 to 15 psi
090	0 to 30 psi
100	0 to 60 psi
110	0 to 100 psi
120	0 to 160 psi
130	0 to 200 psi
140	0 to 300 psi

Range Codes	Specific Ranges
150	0 to 400 psi
160	0 to 600 psi
180	0 to 1000 psi
190	0 to 1500 psi
200	0 to 2000 psi
210	0 to 3000 psi
220	0 to 5000 psi

